

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B01D 53/86, B60R 16/08, F15B 21/04	A1	(11) International Publication Number: WO 00/66251 (43) International Publication Date: 9 November 2000 (09.11.00)
(21) International Application Number: PCT/SE00/00638 (22) International Filing Date: 4 April 2000 (04.04.00) (30) Priority Data: 9901355-9 16 April 1999 (16.04.99) SE (71) Applicant (for all designated States except US): VOLVO LASTVAGNAR AB [SE/SE]; S-405 08 Göteborg (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): SABELSTRÖM, Mats [SE/SE]; Lilla Mellanbergsvägen 3, S-427 37 Billdal (SE). MEGAS, Lucas [SE/SE]; Bovallstrandsgatan 28, S-416 74 Göteborg (SE). (74) Agent: ALBIHNS PATENTBYRÅ GÖTEBORG AB; P.O. Box 142, S-401 22 Göteborg (SE).		(81) Designated States: US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. In English translation (filed in Swedish).

(54) Title: AIR COMPRESSION ARRANGEMENT FOR VEHICLES



(57) Abstract

The invention relates to an arrangement for a compressed-air system (1) in a vehicle, comprising a connection (6, 10) for feeding compressed air from a compressor (2) to the rest of the compressed-air system. The invention is characterized in that it comprises an oxidation catalyst (9) which is adapted for cleaning the compressed air and which is positioned along said connection (6, 10), said connection (6, 10) comprising a line (10) which is connected between the oxidation catalyst (9) and the rest of the compressed-air system. The invention provides an improved arrangement for cleaning compressed air in a compressed-air system for a vehicle.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Air compression arrangement for vehicles.

TECHNICAL FIELD

The present invention relates to an arrangement for a
5 compressed-air system in a vehicle, according to the
precharacterizing clause of Patent Claim 1 below. The
invention is intended in particular for use in
compressed-air systems in heavy-duty lorries.

10 BACKGROUND ART

In connection with a vehicle which is provided with a
compressed-air system for producing, storing and
distributing compressed air to, for example, the air
suspension system and the brake system, which in a manner
15 known per se includes pressure tanks, compressed-air
lines and various types of valve, said system is supplied
with compressed air from a compressed-air compressor.
Said compressor is driven in a manner known per se by
means of the internal combustion engine of the vehicle.
20 To lubricate the compressor, use is made, according to
the known art, of lubricating oil from the lubricating
oil system of the internal combustion engine.

In accordance with previously known art, the compressed
25 air can be fed from the compressor to the compressed-air
system of the vehicle. A problem which occurs in
previously known compressed-air systems of the
abovementioned type is that the compressed air which is
generated in the compressor is often contaminated by
30 lubricating oil in aerosol and gaseous form. During
operation of the compressor, a very high temperature is
reached, which can lead to oxidation of the lubricating
oil mixed into the compressed air, which can result in
polymerization of the oil and the formation of aggressive
35 oxidation products. If these contaminants were to be
conveyed to the rest of the compressed-air system of the

vehicle, coatings could be formed in the components of said system. These coatings can cause clogging and corrosion of the material of said components, which can in turn cause failure of the components.

5

According to the known art, the compressed air generated in the compressed-air compressor can be cleaned by means of a mechanical filter combined with cooling. A disadvantage of this technique, however, is its low degree of efficiency.

10

DISCLOSURE OF INVENTION

The object of the present invention is to provide an arrangement for efficient cleaning of compressed air in a compressed-air system for a vehicle, in particular for a compressed-air system in which the compressed air is generated by a compressor which is lubricated by lubricating oil from an internal combustion engine. This is achieved by means of an arrangement, the features of which emerge from Patent Claim 1 below.

15
20

The invention constitutes an arrangement for a compressed-air system in a vehicle and comprises a connection for feeding compressed air from a compressor to the rest of the compressed-air system. The invention is characterized in that it comprises an oxidation catalyst which is adapted for cleaning the compressed air and which is positioned along said connection, said connection comprising a line which is connected between the oxidation catalyst and the rest of the compressed-air system.

25
30

Advantageous embodiments of the invention emerge from the dependent patent claims below.

35

BRIEF DESCRIPTION OF DRAWINGS

The invention will be explained in greater detail below with reference to a preferred illustrative embodiment and the appended Figure 1 which is a basic diagram of an arrangement according to the present invention.

MODE FOR CARRYING OUT THE INVENTION

Fig. 1 is a basic diagram of an arrangement according to the present invention. According to a preferred embodiment, the arrangement is used in connection with a compressed-air system 1 of a type known per se, which may preferably but does not have to consist of a compressed-air system for a lorry. The compressed-air system 1, which comprises, for example, a pressure tank and also the air-suspension system and the brake system of the vehicle, is reproduced in a greatly simplified manner in Figure 1.

Compressed air in the compressed-air system 1 is generated in a compressor 2 which is mechanically connected to an internal combustion engine 3 via a transmission 4. In this way, the air flowing from the atmosphere, as indicated by an arrow in the figure, and to the compressor 2 via an air intake line 5, can be compressed and fed out in a line 6. The compressor 2 is supplied with lubricating oil from the lubricating oil system 7 of the internal combustion engine 3 via a separate line 8 which is connected to the compressor 2.

When the compressor is in operation, a very high temperature is generated in it, which causes oxidation of the lubricating oil mixed into the compressed air. The aggressive oxidation products then formed, for example esters, resin-like substances and aerosols, can contaminate the compressed air generated in the compressor 2. If this contaminated compressed air were to

be fed to the compressed-air system 1, it could form coatings on pressure tanks and the like and bring about clogging of valves and material corrosion. For this reason, it is a fundamental principle of the present invention that the contaminated compressed air is led from the compressor 2 to an oxidation catalyst 9 via the line 6 connected to it from the compressor 2. In the oxidation catalyst 9, the contaminants contained in the compressed air will be converted to carbon dioxide and water. The cleaned compressed air is then conveyed to the compressed-air system 1 by means of another line 10.

The oxidation catalyst 9 is designed in such a manner that it has a given minimum limit temperature at which it is capable of working with satisfactory cleaning capacity. This limit temperature is usually of the order of roughly 200°C. In order to guarantee the desired limit temperature, the invention can be adapted so that the oxidation catalyst 9 comprises heating means. This can in turn be brought about by the oxidation catalyst 9 being designed with an electric heating arrangement, in which way it is possible to ensure that the desired temperature of the oxidation catalyst 9 can be reached.

It may be pointed out, however, that the correct working temperature is reached in the oxidation catalyst 9 during normal operation of the compressor 2 without a separate heating arrangement, because the compressed air generated in the compressor 2 reaches a very high temperature.

The invention is not limited to the embodiment described above but can be varied within the scope of the patent claims below. For example, the invention can be used in different types of vehicle, for example private cars, lorries, loading machines and buses, which comprise a

compressor for generating compressed air for a
compressed-air system.

PATENT CLAIMS

1. Arrangement for a compressed-air system (1) in a vehicle, comprising a connection (6, 10) for feeding
5 compressed air from a compressor (2) to the rest of the compressed-air system, characterized in that it comprises an oxidation catalyst (9) which is adapted for cleaning the compressed air and which is positioned along said connection (6, 10), said connection (6, 10) comprising a
10 line (10) which is connected between the oxidation catalyst (9) and the rest of the compressed-air system.
2. Arrangement according to Patent Claim 1, characterized in that the oxidation catalyst (9) can be
15 heated.
3. Arrangement according to Patent Claim 2, characterized in that the oxidation catalyst (9) can be heated by means of an electric heating arrangement.
20
4. Arrangement according to any one of the preceding patent claims, characterized in that the engine (3) consists of a diesel engine.

1/1




FIG.1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00638

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B01D 53/86, B60R 16/08, F15B 21/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B01D, B50G, B60K, B60R, B60T, B60V, F15B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 19515895 A1 (ROBERT BOSCH GMBH), 31 October 1996 (31.10.96), claim 1 --	1
A	US 5182086 A (C.A. HENDERSON ET AL), 26 January 1993 (26.01.93), abstract --	1
A	US 5409514 A (G. RAGUSA ET AL), 25 April 1995 (25.04.95), abstract --	1
A	US 5906480 A (M. SABELSTRÖM ET AL), 25 May 1999 (25.05.99), figure 1, abstract -- -----	1

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 June 2000

Date of mailing of the international search report

25 -07- 2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Lena Nilsson / Mrs

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SE 00/00638

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19515895 A1	31/10/96	CN 1181043 A DE 59601057 D EP 0827470 A,B SE 0827470 T3 JP 11504294 T WO 9634785 A	06/05/98 00/00/00 11/03/98 20/04/99 07/11/96
US 5182086 A	26/01/93	US 5284629 A	08/02/94
US 5409514 A	25/04/95	AT 140396 T AU 653063 B BR 9206446 A CA 2116430 A DE 69212335 D,T EP 0640002 A,B SE 0640002 T3 JP 6510229 T WO 9304761 A	15/08/96 15/09/94 13/12/94 18/03/93 02/01/97 01/03/95 17/11/94 18/03/93
US 5906480 A	25/05/99	AU 1829395 A DE 69510177 D,T EP 0740622 A,B JP 9509119 T SE 9400575 A WO 9522474 A SE 511644 C SE 9500168 A	04/09/95 18/11/99 06/11/96 16/09/97 19/08/95 24/08/95 01/11/99 20/07/96

